



Industrial
Lubricants



Automotive
Lubricants



Biodegradable
Lubricants



Agricultural
Lubricants



Cleaning &
Maintenance



Greases &
Pastes



Foodsafe
Lubricants



Heritage Oils



Lubrication
Equipment



Metalworking
Fluids



Gear Oils SAE

Straight Non EP Gear Oils
Product Code: A20, A2E

Product Description

Pennine Gear Oil SAE 90 and SAE 80 are manufactured from selected solvent refined base stocks and is non-additive treated to meet the API GL1 service classification.

Applications

These products are recommended for use in automotive spiral bevel, and worm gear axle units where EP Oils are not considered either necessary, or in some instances, desirable.

Performance Specifications

Meets the Requirements of API service classification GL1.

Typical Test Data

	A20	A2E
SAE classification	90	80
K. V. @ 100° C (cSt)	17.0	10.2
K. V. @ 40° C (cSt)	189	80
Viscosity Index	96	96
Density @ 15° C	0.89	0.88
Flash Point (°C)	245	205
Pour Point (°C)	-9	-18

Availability

Pennine Gear Oil SAE 90 is available in bulk, 205 litre barrels, 25 litre drums and 10 litre, 5 litre, 1 litre and 500ml plastic bottles.

Storage

Barrels of lubricant should always be stored in such a way that will prevent the ingress of water when stored in the open.

Health & Safety

Please refer to the relevant Health and Safety Data Sheet, a copy of which is freely available to all our customers.

Data represented is typical of that obtained with normal production tolerances and does not constitute a specification. The policy of Pennine Lubricants is one of continual improvement, we therefore reserve the right to change specifications without notice.



Certificate Number: 9480
ISO 9001



Pennine Lubricants Limited Company reg no. 3510091



32 Atlas Way,
Sheffield, S4 7QQ

T. 0114 285 2987
E. info@penninelubricants.co.uk
W. www.penninelubricants.co.uk