

Section 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier****Product name:** SLIDEWAY OIL TX 32, 68, 100, 150, 220**Product code:** AA0-4**1.2. Relevant identified uses of the substance or mixture and uses advised against****Use of substance / mixture:** Lubricating oil.**1.3. Details of the supplier of the safety data sheet****Company name:** Pennine Lubricants Limited
Unit 35 Limestone Cottage Lane
Sheffield
South Yorkshire
S6 1NJ
United Kingdom**Tel:** 0114 285 2987**Fax:** 0114 285 2988**Email:** info@penninelubes.plus.com**1.4. Emergency telephone number****Emergency tel:** 0114 285 2987 (Office hours only)**Section 2: Hazards identification****2.1. Classification of the substance or mixture****Classification under CLP:** This product has no classification under CLP.**2.2. Label elements****Label elements:** This product has no label elements.**2.3. Other hazards****PBT:** This product is not identified as a PBT/vPvB substance.**Section 3: Composition/information on ingredients****3.2. Mixtures****Section 4: First aid measures****4.1. Description of first aid measures****Skin contact:** Wash immediately with plenty of soap and water.**Eye contact:** Bathe the eye with running water for 15 minutes.

SAFETY DATA SHEET

SLIDEWAY OIL TX 32, 68, 100, 150, 220

Page: 2

Ingestion: Wash out mouth with water.

Inhalation: Get medical attention if symptoms occur.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be irritation of the throat.

Inhalation: No symptoms.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Not applicable.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Carbon dioxide. Alcohol resistant foam. Dry chemical powder. Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Spillages may be slippery. Refer to section 8 of SDS for personal protection details. Turn leaking containers leak-side up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed.

[cont...]

SAFETY DATA SHEET

SLIDEWAY OIL TX 32, 68, 100, 150, 220

Page: 3

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Workplace exposure limits: No data available.

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Respiratory protection: Respiratory protection not required.

Hand protection: Gloves (oil-resistant).

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Yellow-brown

Odour: Characteristic odour

Evaporation rate: Negligible

Solubility in water: Insoluble

Also soluble in: Most organic solvents.

Viscosity: Viscous

Kinematic viscosity: As Grade

Viscosity test method: Kinematic Viscosity at 40C (cSt)

Boiling point/range°C: >250

Flash point°C: >200

Relative density: 0.875-0.9

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

[cont...]

SAFETY DATA SHEET

SLIDEWAY OIL TX 32, 68, 100, 150, 220

Page: 4

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Toxicity values: No data available.

Symptoms / routes of exposure

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be irritation of the throat.

Inhalation: No symptoms.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: No data available.

12.2. Persistence and degradability

Persistence and degradability: Inherently biodegradable

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

Waste code number: 13 02 05

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

[cont...]

SAFETY DATA SHEET

SLIDEWAY OIL TX 32, 68, 100, 150, 220

Page: 5

Section 14: Transport information

Transport class: This product does not require a classification for transport.

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010.

* indicates text in the SDS which has changed since the last revision.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.