



Industrial
Lubricants



Automotive
Lubricants



Biodegradable
Lubricants



Agricultural
Lubricants



Cleaning &
Maintenance



Greases &
Pastes



Foodsafe
Lubricants



Heritage Oils



Lubrication
Equipment



Metalworking
Fluids



Super Mould Oil

Low Odour Concrete Mould Release Agent

Product Code: ACB

Product Description

Pennine Super Mould Oil is a low viscosity concrete mould release agent formulated from non-hazardous raw materials. This product is classed as a chemical mould release agent as it includes specially designed components to help to “chemically” release the casting from the mould or form.

Applications

Super Mould Oil is supplied ready to use and is suitable for virtually all types of mould and form face material including steel, timber and most plastics. It can be applied by brush, swab or spray, and is designed to give a good surface finish with easy removal.

Typical Test Data

	ACB
Density @ 15°C	0.84
K. V. @ 40°C cSt	6

Availability

Pennine Super Mould Oil is available in bulk, 1000 litre IBC's, 205 litre barrels, 25 litre drums and 5 litre plastic bottles.

Storage

Barrels of lubricant should always be stored in such a way that will prevent the ingress of water when stored in the open.

Health and Safety

Please refer to the relevant Health and Safety Data Sheet, a copy of which is freely available to all our customers.

Data represented is typical of that obtained with normal production tolerances and does not constitute a specification. The policy of Pennine Lubricants is one of continual improvement; we therefore reserve the right to change specifications without notice.



Certificate Number: 9480
ISO 9001



Pennine Lubricants Limited Company reg no. 3510091



32 Atlas Way,
Sheffield, S4 7QQ

T. 0114 285 2987
E. info@penninelubricants.co.uk
W. www.penninelubricants.co.uk