

Section 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier****Product name:** ULTRASOL X-3203**Product code:** AXB**1.2. Relevant identified uses of the substance or mixture and uses advised against****Use of substance / mixture:** PC25: Metal working fluids.**1.3. Details of the supplier of the safety data sheet****Company name:** Pennine Lubricants Limited

32 Atlas Way

Sheffield

South Yorkshire

S4 7QQ

United Kingdom

Tel: 0114 285 2987**Email:** info@penninelubricants.co.uk**1.4. Emergency telephone number****Emergency tel:** 0114 285 2987 (Office hours only)**Section 2: Hazards identification****2.1. Classification of the substance or mixture****Classification under CLP:** Eye Dam. 1: H318; Skin Irrit. 2: H315**Most important adverse effects:** Causes skin irritation. Causes serious eye damage.**2.2. Label elements****Label elements:****Hazard statements:** H315: Causes skin irritation.

H318: Causes serious eye damage.

Hazard pictograms: GHS05: Corrosion**Signal words:** Danger**Precautionary statements:** P273: Avoid release to the environment.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P391: Collect spillage.

P302+P352: IF ON SKIN: Wash with plenty of water.

SAFETY DATA SHEET

ULTRASOL X-3203

Page: 2

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310: Immediately call a POISON CENTER or doctor.

P321: Specific treatment (see supplemental first aid instruction on this label)

P362+P364: Take off contaminated clothing and wash it before reuse.

P501: Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

2-PHENOXYETHANOL

EINECS	CAS	PBT / WEL	CLP Classification	Percent
204-589-7	122-99-6	-	Acute Tox. 4: H302; Eye Irrit. 2: H319	1-10%

ALKYLETHER CARBOXYLIC ACID NEUTRALISED

-	POLYMER	-	Skin Irrit. 2: H315; Eye Irrit. 2: H319	1-10%
---	---------	---	---	-------

SULPHONIC ACIDS, PETROLEUM, SODIUM SALTS - REACH registered number(s): 01-2119527859-22-XXXX

271-781-5	68608-26-4	-	Eye Irrit. 2: H319	1-10%
-----------	------------	---	--------------------	-------

DISTILLED TALL OIL NEUTRALISED WITH ALKYLAMINE

-	-	-	Acute Tox. 4: H312; Skin Irrit. 2: H315; Eye Dam. 1: H318; Aquatic Chronic 3: H412	1-10%
---	---	---	--	-------

POLYCARBOXYLIC ACID NEUTRALISED WITH ALKYLTRIAMINE

-	-	-	Acute Tox. 4: H312; Skin Irrit. 2: H315; Eye Dam. 1: H318; Aquatic Chronic 3: H412	1-10%
---	---	---	--	-------

PHOSPHATE ESTER NEUTRALISED WITH ALKYLTRIAMINE

-	-	-	Acute Tox. 4: H302; Skin Irrit. 2: H315; Eye Dam. 1: H318; Aquatic Chronic 3: H412	1-10%
---	---	---	--	-------

2,2'-IMINODIETHANOL

203-868-0	111-42-2	-	Acute Tox. 4: H302; STOT RE 2: H373; Skin Irrit. 2: H315; Eye Dam. 1: H318	1-10%
-----------	----------	---	--	-------

[cont...]

SAFETY DATA SHEET

ULTRASOL X-3203

Page: 3

ALCOHOLS, C9-11 ETHOXYLATED

-	68439-46-3	-	Eye Dam. 1: H318; Acute Tox. 4: H302	1-10%
---	------------	---	--------------------------------------	-------

ALCOHOLS C11-C14 ISO C13 RICH - REACH registered number(s): 01-2119454259-32-0000

271-235-6	68526-86-3	-	Aquatic Acute 1: H400	1-10%
-----------	------------	---	-----------------------	-------

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist examination.

Ingestion: Wash out mouth with water. Do not induce vomiting. If conscious, give half a litre of water to drink immediately. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be pain and redness. The eyes may water profusely. There may be severe pain. The vision may become blurred. May cause permanent damage.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Carbon dioxide. Alcohol resistant foam. Dry chemical powder.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Spillages may be slippery. Mark out the contaminated area with signs and prevent

[cont...]

SAFETY DATA SHEET

ULTRASOL X-3203

Page: 4

access to unauthorised personnel. Do not attempt to take action without suitable protective clothing - see section 8 of SDS. Turn leaking containers leak-side up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.
Avoid the formation or spread of mists in the air.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

2-PHENOXYETHANOL

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	110 mg/m ³	110 mg/m ³	-	-

2,2'-IMINODIETHANOL

UK	13 mg/m ³	-	-	-
----	----------------------	---	---	---

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Protective gloves.

[cont...]

SAFETY DATA SHEET

ULTRASOL X-3203

Page: 5

Eye protection: Tightly fitting safety goggles. Ensure eye bath is to hand.

Skin protection: Protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Amber

Odour: Characteristic odour

Solubility in water: Miscible

Viscosity: Viscous

Boiling point/range°C: >100

Flash point°C: >100

Relative density: 0.995

pH: 10.5

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.
Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

[cont...]

SAFETY DATA SHEET

ULTRASOL X-3203

Page: 6

2-PHENOXYETHANOL

ORL	MUS	LD50	933	mg/kg
ORL	RAT	LD50	1260	mg/kg
SKN	RAT	LD50	14422	mg/kg

2,2'-IMINODIETHANOL

IVN	RAT	LD50	778	mg/kg
ORL	MUS	LD50	3300	mg/kg
ORL	RAT	LD50	620	µl/kg
SCU	RAT	LD50	2200	mg/kg

Relevant hazards for product:

Hazard	Route	Basis
Skin corrosion/irritation	DRM	Hazardous: calculated
Serious eye damage/irritation	OPT	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be pain and redness. The eyes may water profusely. There may be severe pain. The vision may become blurred. May cause permanent damage.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: No data available.

12.2. Persistence and degradability

Persistence and degradability: Inherently biodegradable

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

[cont...]

SAFETY DATA SHEET

ULTRASOL X-3203

Page: 7

12.6. Other adverse effects

Other adverse effects: Toxic to aquatic organisms.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

Waste code number: 12 01 07

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

Transport class: This product does not require a classification for transport.

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

Section 16: Other information

Other information

Other information: according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

* indicates text in the SDS which has changed since the last revision.

Guidance on the use of metalworking fluids in the UK can be found at:

<http://www.ukla.org.uk/wp-content/uploads/UKLA-HSE-Good-Practice-Guide-for-Safe-Handling-and-Disposal-of-Metalworking-Fluids.pdf>

Phrases used in s.2 and s.3: H302: Harmful if swallowed.

H312: Harmful in contact with skin.

H315: Causes skin irritation.

H318: Causes serious eye damage.

H319: Causes serious eye irritation.

H373: May cause damage to organs through prolonged or repeated exposure.

H400: Very toxic to aquatic life.

H412: Harmful to aquatic life with long lasting effects.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.