



Industrial
Lubricants



Automotive
Lubricants



Biodegradable
Lubricants




Agricultural
Lubricants



Cleaning &
Maintenance




Greases &
Pastes




Foodsafe
Lubricants



Heritage Oils



Lubrication
Equipment



Metalworking
Fluids



Ultrasyne PRO-S 5w/30

High performance Low SAPS Full Synthetic Motor Oil

Product Code: A0Q

Product Description

Pennine Ultrasyne PRO-S 5w/30 is a low SAPS (sulphated ash phosphorous and sulphur) full synthetic high performance engine oil designed to support flexible extended oil drain intervals (ODI) in accordance with vehicle manufacturers recommendations. The synthetic base and specially selected additives incorporated in the product offers the highest possible protection, cleanliness and performance. The product offers excellent cold start protection, tremendous film strength and outstanding performance.

Applications

Recommended for use in passenger cars and light duty commercial vehicles both petrol and diesel, naturally aspirated and turbocharged. Specially formulated to meet Mercedes Benz MB 229.31 and BMW Longlife – 04 specification. The high specification of this product makes it suitable for all vehicles requiring an oil meeting ACEA A3/B3/B4/C3 standards.

Performance Specifications

This product meets or exceeds the performance requirements of major motor manufacturers and the following specifications: -

MB 229.31 (backwards compatible with MB 229.3)

BMW Longlife –04 (backwards compatible with BMW Longlife – 01)

ACEA C3

API SM/CF

Typical Test Data

	A0Q
SAE classification	5W/30
K. V. @40° C (cSt)	72.3
K. V. @ 100° C (cSt)	11.8
Viscosity Index	160
Flash Point (°C)	212
Sulphated Ash (% weight)	0.773
TBN (mg KOH / g)	7.8



Certificate Number: 9480
ISO 9001



Pennine Lubricants Limited Company reg no. 3510091




32 Atlas Way,
Sheffield, S4 7QQ

T. 0114 285 2987

E. info@penninelubricants.co.uk

W. www.penninelubricants.co.uk

Industrial
LubricantsAutomotive
LubricantsBiodegradable
LubricantsAgricultural
LubricantsCleaning &
MaintenanceGreases &
PastesFoodsafe
Lubricants

Heritage Oils

Lubrication
EquipmentMetalworking
Fluids

Ultrasyn PRO-S 5w/30

High performance Low SAPS Full Synthetic Motor Oil
Product Code: A0Q

Availability

Pennine Ultrasyn PRO-S 5w/30 is available in bulk, 1000 litre IBC's, 205 litre barrels, 25 litre drums, 5 litre and 1 litre plastic bottles.

Storage

Barrels of lubricant should always be stored in such a way that will prevent the ingress of water when stored in the open.

Health & Safety

Please refer to the relevant Health and Safety Data Sheet, a copy of which is freely available to all our customers.

Data represented is typical of that obtained with normal production tolerances and does not constitute a specification. The policy of Pennine Lubricants is one of continual improvement, we therefore reserve the right to change specifications without notice.



Certificate Number: 9480
ISO 9001



Pennine Lubricants Limited Company reg no. 3510091



32 Atlas Way,
Sheffield, S4 7QQ

T. 0114 285 2987
E. info@penninelubricants.co.uk
W. www.penninelubricants.co.uk