



Industrial
Lubricants



Automotive
Lubricants



Biodegradable
Lubricants



Agricultural
Lubricants



Cleaning &
Maintenance



Greases &
Pastes



Foodsafe
Lubricants



Heritage Oils



Lubrication
Equipment



Metalworking
Fluids



Vistapro NT 22

Napthenic Process Oil
Product Code: ACS

Product Description

Pennine Vistapro NT 22 is a premium quality process lubricant manufactured from highly refined napthenic base stocks. The product has inherently good resistance to oxidation, good demulsification properties, excellent thermal stability, low foaming tendencies and excellent solvency properties.

Applications

Recommended for use as carrier or extender fluids in manufacturing processes including rubber, elastomer, plastics, adhesive and other applications where a napthenic oil is desirable.

Typical Test Data

	ACS
Viscosity Classification	22
Density @ 20°C	0.90
K. V. @ 40°C cSt	22
K. V. @ 100°C cSt	3.7
Flash Point (IP35) °C	170
Pour Point (IP15) °C	-45

Availability

Pennine Vistapro NT 22 is available in bulk, 1000 ltr IBC's, 205 litre barrels and 25 litre drums.

Storage

Barrels of lubricant should always be stored in such a way that will prevent the ingress of water when stored in the open.

Health and Safety

Please refer to the relevant Health and Safety Data Sheet, a copy of which is freely available to all our customers. Data represented is typical of that obtained with normal production tolerances and does not constitute a specification. The policy of Pennine Lubricants is one of continual improvement; we therefore reserve the right to change specifications without notice.



Certificate Number: 9480
ISO 9001



Pennine Lubricants Limited Company reg no. 3510091



32 Atlas Way,
Sheffield, S4 7QQ

T. 0114 285 2987
E. info@penninelubricants.co.uk
W. www.penninelubricants.co.uk