Industrial Lubricants
Automotive Lubricants
Biodegradable Lubricants
Agricultural Lubricants
Cleaning & Maintenance
Greases & Pastes
Foodsafe Lubricants
Heritage Oils
Lubrication Equipment
Metalworking Fluids

Bakery Chain Lubricant (Graphited)

High Temperature Industrial Chain Lubricant

Product Description

Pennine Bakery Chain Lubricant (Graphited) is a high temperature, non-toxic, chain lubricant. Manufactured using high quality polyalkylene glycol base oil with a careful balance of graphite the product exhibits excellent high temperature performance characteristics.

Applications

Pennine Bakery Chain Lubricant (Graphited) is particularly suitable for use in high temperature bakery oven chains whereby the graphite within the formulation assists in retaining good lubrication performance even after the high temperature synthetic base oil has evaporated. The product is also suitable for use in other high temperature chain applications used throughout industry such as paint plants, heat treatments plants and kiln car tracks.

Typical Test Data

Appearance	Black Liquid
Graphite Content %	15
Application Range °C	0 - 180
Operating Temperature °C	Up to 650
Density @ 15°C	1.1
K.V. @ 20°C	3600 cP
Viscosity Index	120
Boiling Point °C	100
Flash Point °C	> 235

32 Atlas Way,
Sheffield, S4 7QQ

T. 0114 285 2987
E. info@penninelubricants.co.uk
W. www.penninelubricants.co.uk

Industrial Lubricants
Automotive Lubricants
Biodegradable Lubricants
Agricultural Lubricants
Cleaning & Maintenance
Greases & Pastes
Foodsafe Lubricants
Heritage Oils
Lubrication Equipment
Metalworking Fluids

Bakery Chain Lubricant (Graphited)

High Temperature Industrial Chain Lubricant

Availability

Pennine Bakery Chain Lubricant (Graphited) is available in 25 litre drums and 5 litre bottles.

Storage

Barrels of lubricant should always be stored in such a way that will prevent the ingress of water when stored in the open.

Health & Safety

Please refer to the relevant Health and Safety Data Sheet, a copy of which is freely available to all our customers.

Data represented is typical of that obtained with normal production tolerances and does not constitute a specification. The policy of Pennine Lubricants is one of continual improvement, we therefore reserve the right to change specifications without notice.

32 Atlas Way,
Sheffield, S4 7QQ

T. 0114 285 2987
E. info@penninelubricants.co.uk
W. www.penninelubricants.co.uk